MANNOL Compressor Oil ISO 150

2903

Highly-purified paraffin low-ash mineral compressor oil with an extended replacement age. It ensures a stable and continuous operation of the equipment throughout the entire operation period.

Product properties:
- They contain antifriction, antiwear, anti-oxidising, anticorrosion and antifoaming additives;
- An excellent thermal stability;
- Great antiwear properties;
- An exceptional resistance to oxidisation and ageing;
- A minimal formation of deposits and sediments: it guarantees the cleanliness of all mechanical parts, prevents the risk of fire or explosion;
- It has excellent anticorrosion and antifoaming properties and a low evaporation capacity;
- They are recommended for use at ambient temperatures of -25 °C and up;
- They have excellent cooling properties;
- They are compatible with all sealing materials;
- The replacement period up to 4,000 running hours.

Use: all types of air piston-type (moderate and heavy operating modes) and air rotary (moderate operating mode) compressors with the outlet air temperature up to 220 °C. They are recommended for long life compressors.
It can be used in hydraulic systems as a low-ash oil.
In order to properly use them, thoroughly read the user's manual of the equipment.

Recommendation
ISO Viscosity Grade 150
DIN 51506 (VBL)
DIN 51506 (VCL)
DIN 51506 (VDL)
ISO DP 6521 L-DAA
ISO DP 6521 L-DAB
ISO DP 6521 L-DAG
ISO DP 6521 L-DAH

PACKAGING

60L	MN2903-60	Drum	
208L	MN2903-DR	Drum	
20L	MN2903-20	Plastic	
10L	MN2903-10	Plastic	